

ABLE

No Buff Floor & Terrazzo Finish/ Sealer. Low Maintenance – Durable & Long Wearing- Resists Black Marks.

High Gloss. Resistant to Detergents, Wear, Abuse & Neglect.

Easily Repair-ABLE.

DESCRIPTION

ABLE @ 18% nano-polymer solids, represents the latest technology and most significant advances in floor finishes...ever! This new chemistry results in exceptional gloss and durability with scuff and black heel mark resistance second to none. ABLE wears well in brutal floor traffic and under wheel traffic. ABLE is designed for use with conventional-to-ultra-high speed propane equipment. Dries and levels evenly into a super hard gloss that is easily removed via W.O.W! Branded Products.

DIRECTIONS

Floor should be clean and free of all soil, residue and debris. A properly prepared floor should be rinsed thoroughly, and allowed to dry. Stripped Floors should be neutralized with either W.O.W! Brand Neutra-Clean, KNAAK, or Issac Neutralize, and allowed to dry. Using a clean finish mop or applicator, apply five (5) light to three (3) medium coats of ABLE. Allow 30 minutes to dry between coats. Allow extra drying time under conditions of extreme humidity and/or poor ventilation. To achieve maximum gloss, wait 24 hours then apply two (2) additional coats of ABLE, after the floor has been cleaned of all debris, soil, and residue using W.O.W! Brand Neutra-Clean, KNAAK, Issac Neutralize or W.O.W! Brand Commercial Hi Flow Dilution #1, to label directions. ABLE should not be buffed immediately after application. Forced air drying of ABLE or any floor finish is not recommended. If a BAsse Cote is warranted, we recommend our BAsse Cote with a clean synthetic mop or applicator with 2 layers

Do not exceed 2 layers. Allow layer to dry thoroughly between coats. You can hi speed or propane burnish dried layers of BAsse Cote between coats

Recommended Daily Maintenance:

- Dust Mopping daily to remove surface soil and minimize abrasion due to soil
- Use a W.O.W! Brand recommended cleaner, or germicidal detergent mop or autoscrub-white or red pad-light to medium pressure.
- If your program includes buffing or burnishing, consult your W.O.W! Brand Representative or distributor for proper machine maintenance procedures, including HONEST and or Standing Ovation.

Restorative Maintenance

- Scrub floor with floor machine or autoscrubber using W.O.W! Brand W.O.W! Commercial #2 or KNAAK at 2 oz per gallon.
- Rinse thoroughly with clean water. Allow to dry!
- Using a clean finish mop, evenly apply two(2) thin coats, allowing thirty(30) minutes to dry between coats.

Allow extra time

for drying if conditions of high humidity or poor ventilation warrant.

ABLE is a commercial product not intended for home use. This product meets CSMA floor [polish slip resistance requirements] employing ASTM test method #d-2047

PRECAUTIONS

-Do Not Use Metal Drum Pumps or Buckets

-Do Not Allow Product To Freeze

-CAUTION-May Cause Eye Irritation. Avoid Contact With Eyes

First Aid:

EYE CONTACT-Flush with large amount of water for 15 minutes, lifting upper and lower lids occasionally. Get medical

Attention.

INHALATION-Remove to Fresh Air

SKIN CONTACT-Wash with mild soap and water. remove contaminated clothing and wash before re-use

INGESTION-If conscious, dilute by giving 2 glasses of water and induce vomiting. Keep warm, quiet and call physician

Immediately.

KEEP OUT OF REACH OF CHILDREN

Re-order Product # 976 WHMIS D 2 B

Health 1 Flammability 0 Reactivity 0 PPE A

Coverage 2500-3000 sq ft/gal odor neutral NVS 20%+ - .05% astm Drying 30-45 min.
shelf 1 yr

Mfg Exclusively Under License To:
1.800.535.5053

24/7 emergency INFOTRAC

W.O.W! Brands Inc.

Tonawanda, NY 14150

1.877.792-8389 716.693.2465 Fax 716 693.2467 email

info@wowbrandsinc.com